



- Support 100,000 valid cards & 150,000 records
- Support multiple cards
- Support card, password, fingerprint and combination
- TCP/IP interface to PC
- Wiegand or RS-485 interface to readers(2 door)
- Door time out alarm, intrusion alarm, duress alarm and tamper alarm
- Anti-pass back, multi-door interlock, multi-card open
- Support 128 efficient time and holiday schedules
- Watch dog function ensure device free from halting
- Surface mounted installation

LAK2

Two Door one-way Access Controller



Caratteristiche generali

System

Main Processor	32 Bit
Memory	16M

Input/Output Ports

Input	Inputs x 6 (door sensor x 2, exit button x 2, alarm x 2)
Output	Relay x 4(door lock x 2, alarm x 2)
Reader	Reader x 2

Capacity

Card holders/Events	100,000/150,000
---------------------	-----------------

Function

Access control	Anti-pass back, Multi-interlock, Multi-card unlock
User Management	General, VIP, Guest, Patrol, Black list, Duress
Alarm Function	Door time out alarm, Intrusion alarm, Duress alarm, Tamper alarm
Period	Support 128 groups of schedule, 128 groups of period and 128 groups of holiday period

Interface

To PC	RJ45(10/100M)
To Reader	Wiegand26/34, RS485

Genreal

RTC	Yes
Power Supply	9-15DC/500mA
Operating Temperature	-30°C to +60°C
Working Humidity	≤95%
Dimension(W×D×H)	156mm×51mm×98mm
Weight	0.45kg
Working Environment	Indoor

Certificates

CE	Yes
FCC	Yes

HILTRON LAND S.R.L.

Strada provinciale di Caserta, 218 - 80144 Napoli
 Tel: (+39)081 185 39 000 Fax: (+39)081 185 39 016
www.hiltronsecurty.it