



- Layer two commercial switch
- Supports PoE power management
- Supports wall-mount installation
- Supports anti-theft lock hole
- MAC auto learning and aging, MAC address capacity is 2K
- Supports IEEE802.3, IEEE802.3u and IEEE802.3X standards
- RJ45 port supports 10/100 Mbps self-adaptation
- Supports 250 meters long distance PoE transmission
- Conforms to IEEE802.3af and IEEE802.3at power supply standard.
Port 1 supports Hi-PoE 60W power supply

THSW4P2T

4-Port PoE Switch

Product Overview

THSW4P2T is a 4-port fast ethernet switch, which supports 250 meters long distance PoE transmission. It provides 4*10/100Mbps PoE ports and 2*100 Mbps uplink ports. The product is equipped with two transmission modes (Default/Extend), which are controlled by DIP switch.

Technical Specification

| | |
|------------------------|---|
| Ethernet Port | 2*10/100Mbps Uplink ports 4*10/100 Mbps PoE ports |
| PoE Power Consumption | Port1≤60W, Port2-4≤30W, Total≤60W |
| PoE PIN Assignment | 1, 2, 4, 5 (V+), 3, 6, 7, 8 (V-) |
| PoE Power Management | Support |
| PoE Protocol | IEEE802.3af (PoE), IEEE802.3at (PoE+), Hi-PoE |
| Switching Capacity | 1.8Gbps |
| Packet Forwarding Rate | 90kpps |
| Packet Buffer Memory | 768Kb |
| MAC Table Size | 2K |
| Flow Control | Enable by default |
| Application Humidity | 5%~95% |
| Power | DC 48~57V power adapter |
| Lightning Protection | Common Mode 2KV |
| | Differential Mode 1KV |
| ESD Protection | Air Discharge 8KV Contact Discharge 6KV |
| Working Temperature | -10°C~55°C |
| Weight | 290g |
| Dimension | 130mm×85mm×26mm |

HILTRON LAND SRL

Strada provinciale di Caserta, 218 - 80144 Napoli

Tel: (+39)081 185 39 000 Fax: (+39)081 185 39 016

www.hiltronsecurity.it