



Features:

Keyboard to Control

· High Speed Dome

· Standalone DVR

Connection

· RS485, RS422, USB & RS232

Functions

· Three Dimensional Joystick Control of PTZ Functions

· Preset Position, Auto Scan, Auto Pan, Auto Tour & Pattern Auxiliary Functions

· On-Screen Menu & User Operation Procedure Tips

THKC3VPROV

Network Keyboard & Control Keyboard & Dome keyboard

Caratteristiche Funzionali

General

Keyboard Key panel	Electromechanical
Joystick	3-axis, vector-solving, with twisting, return to-center head
Keyboard Connector	RS232, RS485, RS422, USB
Keyboard Communication	Direct Mode,
Direct Mode	Interface: 1 RS232/2 RS485 Dome Protocol: DH-SD1/PELCO-D/ PELCO-P, etc
Network Mode	N/A
Display	LCD, 75.2mm×33.85mm
Maximum Number of Users	64 (including "admin")

Max RS485 Addresses (Each User)	256
Max Number of PTZ (IPC) That Can be Added over Network (Each User)	2048

Environmental

Power Supply	Power adapter, input 100V~240V 50Hz/60Hz, output DC12V/2A
Power Consumption	5W
Working Temperature	-10°C~+55°C
Working Humidity	10% ~ 90%
Atmosphere Pressure	86kpa~106kpa
Dimension	330mm×160(140)mm×37.5(21)mm (W×D×H)(height: 100mm including joystick)
Weight	2.5kg (Including package)

Hiltron Land S.r.l.

Strada Provinciale di Caserta, 218 80144 - Napoli - Italy

Tel: (+39) 081.185.39.000 Fax: (+39) 081.185.39.016

www.hiltronsecurity.it

