

THC5527SDIR 550TVL 27 x Zoom 80M IR PTZ Camera General Features



- Sony 27X PTZ
- High Speed Dome
- 80m IR Range
- Fully Functional Speed Dome
- 27x Optical Zoom
- External Complete with PSU & Wall Bracket
- Humanity design, novel structure, easy for installation and maintenance
- IR night vision range over 80m
- Horizontal 360°, infinite place, over look 105° (-90° ~ 15°), no blind spot
- Humanize focus and speed proportion
- 128 presets (titles can be set), tour is based on presets, speed & park time of presets can be set
- 8 programmable zones, 4 pattern, and each record time is not less than 180s.
- 4 scan, support scan between left and right limits at an appointed speed.
- Built-in OSD menu, can change information and parameter of dome through menu, also can set and call presets, tour, scan, pattern, camera mode and display name etc
- Park action function, can auto-call presets or start-up tour, pattern and scan after dome idle for a period of time.
- 7 alarm input, 2 alarm output, support linkage. (To call preset pattern, scan, tour, display areas etc)
- Real time function, preset, scan etc action runs based on time sections pre-setting by OSD menu.
- Memory store function, built-in memorizer which can store parameters of camera & functions of PTZ.
- Temperature display function, can survey the temperature inside of dome.
- Fan enable function, through pre-setting the temperature to start-up the fan.
- Display function of Pan/tilt position and zoom, provide a port for motion-tracking and data processing
- Privacy masking zone, you can set masking frame to protect privacy when there is a private zone display onscreen.
- Communication (support RS485, Manchester, BI-PHASE code, coaxial video control).
- Built-in multi-protocols and fully compatible with PELCO-D, PELCO-P, KALATEL, VICON, BOSCH (PHILIPS), SENSORNT, AD, VIDEO B02 etc.
- IP66 all-day protection cover, built-in constant temperature device.

Specification

CCD 1/4" INTERLINE Transfer DSP Samsung SDM-2271 TVL 550TVL Lens 3.5-94.5mm
Minimum Illumination 0.2Lux
Signal to Noise Ratio 2:1 Interlace
Manual Speed Pan: 0.4°~240°/s Tilt: 0.4°~120°/s
Preset Speed H: 240°/s V: 120°/s
Rotation Pan 360° continuously; Tilt 105° (-90° ~ +15°) with auto-flip. Speed Proportion As the length of focus, to auto-adjust the speed
Preset 128 preset, title programmable. Auto-flip Tilt down 90°, with auto-flip 180°. Scan 355° programmable 4 scan
Alarm Function 7 alarm input/2 alarm output (Optional)
D.zoom 16x
Video Output Female BNC
S/N (Y signal) Internal
Auto Electric Shutter Auto/Manual (x128 ~ 1/50sec ~ 1/120,000sec)
Day & Night Auto, COLOR, B/W (IR-CUT) sens x128
OSD Built-In
Motion Detection ON/OFF (output via communication)
Privacy Masking 8 programmable zones with titles
IP Rating IP66
Power Supply AC24V
Weight 7.5kg
Current Consumption 45w Operating Temperature -40 °C to +60 °C